

10462000	DATA SHEET	
Valid from: 18.06.2024	EPIC® H-A 16 AG-LB	

Description

- These connectors are attractive because of their compact housing.
- Small and compact for applications with high number of contacts



General characteristics

Series	H-A 16
Version	Panel mount base
Locking	single lever
Protection (DIN EN 60529)	IP 65 (latched)
Protection (NEMA 250, UL50E)	4, 12 (latched)
Temperature range	-40°C to +100°C, short-term up to +125°C

Materials and surfaces

Housing	Aluminium alloy, powder-coated, grey
Lever	Steel, zinc-plated
Gasket	NBR

Approvals

VDE-Approval, VDE-REG.-Nr.	B437
UL File Number	E75770


Standards

Safety Standard	IEC 61984, UL1977, CSA 22.2 182.3
-----------------	-----------------------------------

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB10462000EN Version: 02	Page 1 of 2
---	---------------------------------------	-------------

10462000	DATA SHEET	
Valid from: 18.06.2024	EPIC® H-A 16 AG-LB	

Drawings



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Compact, robust metal housings size H-A 16

Application range

Machine and equipment manufacturing
Control engineering
Electronic laboratory

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB10462000EN Version: 02	Page 2 of 2
---	---------------------------------------	-------------